

# De Dietrich

## Hood

Ref.: **DHB4674X**

atmosphere of your room and to your needs.



## Product highlights

**Top-of-the-line design** This new hood combines design, technology and functionality. An elegant glass panel, exceptional performances and a host of innovations: discover unrivalled mastery in an exceptional minimalist setting.

**Booster** Thanks to its powerful brushless motor, the hood guarantees rapid elimination of unwanted fumes and odors in intensive mode.

**LED dimmer** This function allows you to adjust the light of your hood on 3 levels in order to adapt it to the

### GENERAL

Brand	DE DIETRICH
Commercial code	DHB4674X
EAN code	3660767999626
Customs code	84146000

### FEATURES

Product type	Wall decorative hood
Design type	Slim box
Width (cm)	60
Finishing	Glass;Body in painted metal
Colour	Black and stainless
Air vented mode	Recycling or extracting air
Delivered in	Air extraction
Type of engine	Brushless
Total power of the motors (W)	160
Number of motors	1
Motor location	In hood
Delayed stop	Yes
LED dimmer	Yes
Fan quantity	1

### PERFORMANCE

Annual energy consumption (kW/h)	40
Energy efficiency class	A+
Min extraction rate (m3/h)	210
Max extraction rate (m3/h)	530
Extraction rate with boost (m3/h)	715
Min recirculation rate (m3/h)	155
Max recirculation rate (m3/h)	521
Recirculation rate with boost (m3/h)	685
Min noise level (dB) (Extraction)	45
Max noise level (dB) (acoustic pressure)	65
Noise level with Boost (dB) (Extraction)	72
Min noise level (dB) (recirculation)	40
Max noise level (dB) (recirculation)	67
Noise level with Boost (dB) (recirculation)	73
Fluid dynamic efficiency class	A
Light efficiency class	A
Lighting efficiency (Lux)	480
Grease filter efficiency class	E

# De Dietrich

## Hood

Ref.: DHB4674X

### CONTROLS & LIGHTS

Control type	Electronic touch-sensitive controls
Number of speed positions (without booster)	3
Booster	Yes
Filters saturation indicator	No
Type of light	LED
Number of lights	2
Total power of the lamps (W)	8

### EQUIPMENT

Type of functions	Speed;Light;Delayed stop
Number of grease filters	2
Grease filter material	Dishwasher safe aluminium
Accessories supplied	Chimney
Reference of charcoal filter	FWK240
Reference of recycling kit	
Optional accessories	Charcoal filter
Reference of engine	
Reference of the chimney extension	
Air outled diameter (mm)	150
Deflector	No
Non-return valve	Yes

### INSTALLATION

Fuse (A)	1.24
Voltage (V)	220-240
Frequency (Hz)	50-60
Other functions	
Dimensions of the product without chimney HxWxD (mm)	40X600X406
Min-max chimney height (mm)	730/935
Dimensions of the packed product HxWxD (mm)	475X700X570
Net weight (kg)	12.3
Gross weight (kg)	15.1

### MANUFACTURING

Availability of spare parts (years)	15
Repair index	